

Pre-Start Checklist

Parking Brakes - SET Battery Switch - OFF Generator Switches - OFF Throttle - IDLE Landing Gear Lever - CHECK DOWN Propeller - HIGH RPM Fuel Condition Lever - FUEL CUTOFF Idle Gate Lever - GROUND IDLE Flaps - UP Battery Switch - ON Panel Lights - AS REQUIRED Fuel Quantity - CHECK Flight controls - CHECK Avionics Master Switch - ON Check Weather (ATIS, Flight Services) Anti-ice - TEST/CHECK Request Clearance

Startup Checklist

Beacon - ON

Transponder - STANDBY

Engine and Propeller Area - CLEAR
Throttle - IDLE
Fuel Valves - OPEN
Fuel Condition Lever - AUTO
Idle Gate Lever - FLIGHT IDLE
Prop Brake - OFF
Engine Start Selection Switch - CRANK
Engine Start Selection Switch - START A+B
Start Button Engine 2 - START (Hold until engine starts)
Generator 2 - ON
Start Button Engine 1 - START (Hold until engine starts)
Generator 1 - ON
Loadmeter & Voltmeter - CHECK FOR CHARGE
Engine Start Selection Switch - OFF

Before Taxi Checklist

Nav Lights - ON
Taxi Lights / Logo Lights / Wing Lights - ON
Heading Indicator/Altimeter - SET
Instruments - NORMAL OPERATION
Radios and Avionics - ON, CHECKED and SET
Autopilot - SET and OFF
F/D - ON
Request Taxi Clearance



Taxi Checklist

Parking Brake - RELEASE
Brakes - CHECK
Directional Gyro - PROPER IND
Turn Coordinator - PROPER IND
Artificial Horizon - ERECT
Taxi to Assigned Runway (Speed Max 20 knots)

Before Take-off Checklist

Parking Brake - SET Fuel Quantity - CHECK Throttle - IDLE Elevator Trim - SET T/O Flaps - 15 Flight Controls - FREE AND CORRECT Engine/Flight Instruments - CHECK Radios and Avionics - SET Landing Lights - ON Taxi Lights - OFF Strobe Light - ON Pitot Heat - ON Anti-Ice - AS REQUIRED Annunciator Lights - CHECK Transponder - ON Request Takeoff Clearance

Take-off Checklist

Brakes - RELEASE
V1 = 105 KIAS (Descision Speed)
Vr = 110 KIAS (Rotate Speed)
Pitch 10-15 deg. nose up
V2 = 115 KIAS (Safety Speed)
Positive Climb Rate - Touch Brakes
Landing Gear - RETRACT
130 KIAS - RETRACT FLAPS
Annunciator Lights/Eng. Instruments - CHECK

Climb-out Checklist

Autopilot - CHECK and SET Yaw Damper - ON Landing Lights - OFF Airspeed 190 KIAS / 1800 fpm 89% above 12'000 ft 180 KIAS / 1500 fpm 77% Engine Instruments - MONITOR ATC - AS REQUIRED



Cruise Checklist (Above FL180)

At Transition Altitude (FL180) set Altimeter to 29,92" (1013mb)
Accelerate to cruise speed;
at 6'000 ft 245 KIAS 78%
at 9'000 ft 240 KIAS 76%
at 12'000 ft 235 KIAS 73%
at 18'000 ft 220 KIAS 68%
at 24'000 ft 205 KIAS 63%
Service Ceiling 25'000 ft
Engine & Instruments - CHECK
Fuel Quantity - CHECK

Descent Checklist

Radios - TUNED and SET Autopilot - CHECK and SET

ATIS/Airport Information - CHECK
Altimeter - CHECK
Radios - SET
Descent Speed - 200 - 240 KIAS
Descent Rate - 1500 fpm
Flaps / Landing Gear - CHECK UP
At Transition Altitude (FL180) - ALTIMITER RESET TO LOCAL
Check Weather (ATIS, Flight Services)

Approach Checklist

Localizer Level Flight

Speed: Establish 160 KIAS 28%

Landing Lights - ON Flaps 15 deg

Speed: Establish 145 KIAS 41% Turning towards runway - FLAPS 30 Speed: Establish 130 KIAS 44%

Landing Gear - DOWN

Final Glideslope Descent

Speed: Establish 120 KIAS 28%

Descent Rate - 600 fpm Elevator Trim - AS DESIRED Parking Brake - VERIFY OFF Anti-Ice - AS REQUIRED Yaw Damper - OFF



Landing Checklist

Landing Gear - CHECK DOWN
Autopilot - OFF
Autothrottle - OFF
Landing Speed - 115 KIAS
After Touchdown - Apply Reverse Thrust
At 60 KIAS - Cancel Reverse Thrust
Spoilers - VERIFY EXTENDED
Brakes - AS REQUIRED

Taxi To Ramp

Strobe Light - OFF
Taxi Lights - ON
Landing Lights - OFF
Flaps - RETRACT
Anti-Ice - OFF
Transponder - 1200
Speed Max - 20 knots
Elevator Trim - TAKEOFF SETTING
Avionics/Radios - AS REQUIRED

Shutdown Checklist

Parking Brake - SET Throttle - IDLE Pitot Heat - OFF F/D - OFF Avionics - OFF Taxi Lights - OFF Logo Lights/Wing Lights - OFF Navigation Lights - OFF Fuel Cond. Lever - FUEL CUTOFF Idle Gate Lever - GROUND IDLE Fuel Valves - CLOSE Beacon - OFF Generators - OFF Prop Brake - ON Panel Light - OFF Battery Switch - OFF

Securing Aircraft Checklist

Parking Brake - SET Throttle - IDLE All Switches - OFF